

Features

- ▶ All-steel 2U/3U durable chassis construction.
- ▶ European and Japanese components ensure optimal result.
- ▶ Soft start upon start-up, overload, overheating, short circuit, DC output, peak voltage limit and intelligent clip protection.
- ▶ Easy detachable amp plate boards help making service jobs easier.
- ▶ High-speed fans start-up for dusting functions and also allows in reducing temperature.
- ▶ LED indicator for monitoring, status and operating modes.

Technical Specifications

Model - Topology H	CQ-804	CQ-1104
No. Of Channels	4	4
MAX Output Power RMS 1KHz		
2Ω	1000 W	1350 W
4Ω	800 W	1100 W
8Ω	425 W	620 W
Bridge 4Ω	2000 W	2700 W
Bridge 8Ω	1600 W	2200 W
Frequency Response Power Bandwidth +/-0.50dB	20Hz-22kHz	
Total Harmonic Distortion 20Hz - 20kHz	0.05%	
Cross Talk 20Hz - 20kHz	≥72dB	
Input Sensitivity @ 8 Ω	1.4V	
Signal-to-Noise-Ratio A Weighted	>101	
Protection Circuits	Short Circuit DC Offset & Overheat	
Rack Mount Space	2U	
Dimensions / W x H x D (mm) / W x H x D (inches)	483x 88 x 406 19 x 3.5 x 16	
Weight	24Kg	
Net / Shipping	26Kg	